

DAD-50

For pharmaceuticals, fine chemicals, and food ingredients purification

DAD series

Preparative Dynamic Axial Compression Column

Model DAD-50 is an automatic packing column developed for high-pressure preparation. Constant pressurization of the packed bed enables self-packing of a high-durability column without creating voids. The slurry port enables operation from supplying of gel to pressurized packing with ease.

Higher sealing performance is achieved by a uniquely developed sealing structure (Japanese Patent No. 3929407). It can be used in a packing cycle for long periods. This column is entirely free from electric parts and therefore, safety use in explosion-proof area is possible. The column, manufactured in Japan, corresponds to IQ/OQ validation. We ensure a thorough support system for the maintenance and supply of consumables.

It is possible to select from various packing materials depending on the preparative object. Preparation and purification will be realized to your satisfaction together with a group of products designed exclusively by YMC.

Main Characteristics

Product number	DAD-50-700S
Inner diameter	50 mm
Packed bed length	100 - 400 mm
Maximum pressure	10 MPa
Compression	Constant pressurization (DAC)
Driving direction	Downward *
Temperature	10 - 40 deg C, Below 50% RH
Installation height	Over 2.5 m
Dimensions	600(W) × 500(D) × 1950(H) mm
Weight	About 50 kg
Utility	0.5 MPa dry air
Maximum Packing material	500 g

Recommended packing material:

Silica, Organic/inorganic hybrid silica 10 µm and larger

Resistance to solvent:

Ordinary solvents used in reversed-phase and normal-phase HPLC

* It is easy to unpack and collect gels from the bottom of the column by moving the cylinder down



Specifications

Name		Preparative Dynamic Axial Compression Column DAD-50
Product number		DAD-50-700S
Body	Size	Inner diameter = $\Phi 50$ mm, Length = 700 mm, Column volume = 1.37 L
	Inner finishing	Electrolytic polishing after honing process
	Roughness	$Ra \leq 0.5$
Filter	Material	SUS316L (Sintered filter)
	Frit size	2 μm
Seal	Material	PTFE
	Type	Movable stopper: Uniquely developed sealing structure End cap: Tighten up with chain clamp
	Feature	Packing seals effectively in response to inner pressure of column Easy replacement
Cylinder	Type	All stainless cylinder
Oil pump	Source	Air-driven hydraulic pump
	Air consumption	MAX 600 L/min (ANR)
Operation	Switching valve	Change orientation of cylinder alignment (UP, DOWN, HOLD)
	Pressure regulator	Control pressure of oil pump
	Pressure meter	Monitoring air operation and oil pressure
Wetted material		SUS316, SUS316L, PTFE, PEEK, PCTFE
Non-wetted material		SUS304, Aluminium, Brass, Steel (Hydraulic equipment parts)
Connection	Inlet/Outlet	1/8" Swagelok tube fitting
	Slurry port	ISO 15A sanitary ferrule
	Air	$\Phi 6$ one-touch fitting

Option

Slurry container	Feature	Slurry can be carried easily
	Product number	SC-2-20
	Pump	Air-driven diaphragm pump Max flow rate 20 L/min
	Air consumption	MAX 200 L/min (ANR)
	Wetted material	SUS316, SUS316L, PTFE, PFA, FEP, SCS14
	Slurry hopper inner finishing	Electrolytic polishing
	Connection	Column connection: ISO 15A sanitary ferrule Air connection: $\Phi 6$ one-touch fitting
Flow path switching panel	Feature	3 three-way valves enable the flow path to be switched easily
Funnel	Material / Connection	SUS316 / ISO15A sanitary ferrule
Cylinder oil		NSF H1 approved oil is available

Before use (installation, operation, maintenance or check-up) of our products, instruction manuals should be carefully read and understood, and safety rules and precautions followed as outlined in the manuals.



YMC CO., LTD.

YMC Karasuma-Gojo Bldg., 284 Daigo-cho
Karasuma Nishiiru Gojo-dori, Shimogyo-ku
Kyoto, 600-8106, Japan
TEL: +81-75-342-4515 FAX: +81-75-342-4550
www.ymc.co.jp sales@ymc.co.jp

Distributor